

SD360 8 Casambi Jumitech EN

English translation generated from the original document.

SD360-8 Casambi

Casambi Ready presence sensor for recessed mounting in suspended ceilings. The sensor covers ø8m at a ceiling height of 2.4m. The sensor features 96 detection zones, making it highly suitable for use in areas with sedentary work. The sensor includes a built-in Casambi module and can therefore be integrated into a wireless Casambi network.

- 3-in-1 sensor – Presence, Lux, Temperature
- Features spring protection to protect soft ceiling tiles
- 96 detection points make it suitable for sedentary work
- Discrete design – only 0.8mm profile thickness

Installation: Detection:

L
N

SD360-8 SD360-8 SD360-8
Casambi Casambi Casambi

Dimensions:

Mounting hole = 56mm

Specifications:

Type SD360-8 Casambi

EAN No. - 5700002215796

Power supply Vac 220 – 240

Frequency range Hz 50/60

Power consumption W 0.100

Lux range (measured at sensor front) Lux 0-4000

Temperature sensor range (measured internally) °C 0-100

Mounting height m 2.4 - 5.0

Detection angle ° 100

Radio transceiver frequency range Ghz 2.400 – 2.483

Max output power radio transceiver dBm +20

Ambient temperature °C +5 - +50

Protection class - IP20

Standards - EN 60669-1, EN 60669-2-1, EN 55015, EN 61547, EN 61000-3-2, EN 61000-3-3, EN 300 328, EN 301 489-1, EN 301 489-17, EN 62479, EN 62493, AS/NZ 4268, FCC PART 15, UL 773A

Rev. 10-23-1.00 Specifications are subject to change without notice

PHONE: +45 20 20 52 54 WWW.JUMITECH.DK E-MAIL: SALG@JUMITECH.DK